AUTODOC CLUB

How to change engine oil and filter on **Audi A4 B5 saloon** – replacement guide

VIDEO TUTORIAL




Important!

This replacement procedure can be used for:
AUDI 80 B3 (89, 89Q, 8A) 2.0 E 16V, AUDI 80 B3 (89, 89Q, 8A) 2.0 E 16V quattro, AUDI 200 C3 Saloon (44, 44Q) 2.2 20V Turbo quattro, AUDI COUPE (89, 8B) 2.0 16 V, AUDI COUPE (89, 8B) 2.6, AUDI COUPE (89, 8B) 2.8, AUDI COUPE (89, 8B) S2 quattro, AUDI COUPE (89, 8B) 2.6 quattro, AUDI COUPE (89, 8B) 2.8 quattro, AUDI 100 C4 Saloon (4A2) 2.0 E, AUDI 100 C4 Saloon (4A2) 2.6, AUDI 100 C4 Saloon (4A2) 2.8 E, AUDI 100 C4 Saloon (4A2) S4 Turbo quattro, AUDI 100 C4 Saloon (4A2) 2.6 quattro, AUDI 100 C4 Saloon (4A2) 2.8 E quattro, (+ 109)

The steps may slightly vary depending on the car design.

REPLACEMENT: ENGINE OIL AND FILTER – AUDI A4 B5 SALOON. TOOLS YOU MIGHT NEED:



- Wire brush
- All-purpose cleaning spray
- Torque wrench
- Combination spanner #19
- Drive socket # 19
- Oil filter cup socket #74-15F
- Ratchet wrench
- Fluid container
- Funnel
- Fender cover

BUY TOOLS

Replacement: engine oil and filter – Audi A4 B5 saloon. AUTODOC experts recommend:

- Replace the oil filter every time when changing motor oil.
- Wear gloves to prevent contact with hot liquid.
- All work should be done with the engine stopped.


REPLACEMENT: ENGINE OIL AND FILTER – AUDI A4 B5 SALOON. USE THE FOLLOWING PROCEDURE:

1 Open the hood.



2 Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.

3 Unscrew the oil filler plug.



4 Lift the car using a jack or place it over an inspection pit.



Replacement: engine oil and filter – Audi A4 B5 saloon. Tip:

- The vehicle must be on even keel, and if it is at an angle, the drain plug must be at the lowest point.
- All works should be done with the engine cooled down.

5 Put a waste oil container with at least 4 l capacity under the drainage hole.




6 Clean the area of the oil pan drainage hole. Clean the oil filter. Use a wire brush. Use all-purpose cleaning spray.



7 Unscrew the drain plug. Use a combination spanner #19.




8 Drain the used oil.




Replacement: engine oil and filter – Audi A4 B5 saloon. Tip from AUTODOC experts:

- Caution! The oil may be hot.

9 Unscrew the oil filter. Use the 74-15F socket. Use a ratchet wrench.




10 Remove the oil filter.



Replacement: engine oil and filter – Audi A4 B5 saloon. AUTODOC recommends:

- Move up the container. The oil starts to drain out of the drainage hole immediately after you have removed the oil filter.


11 Clean the oil filter seat. Use all-purpose cleaning spray.



12 Lubricate the rubber seal of the new filter with a little amount of fresh oil.




13 Install a new oil filter.



Please note!

- Make sure to install the filter correctly. Don't mix up the sides of the part.


14 Tighten the oil filter. Remember to observe the recommended tightening torque. Use the 74-15F socket. Use a torque wrench. Tighten it to 25 Nm torque.




AUTODOC recommends:

- Wait until the oil has completely drained from the drainage hole.


15 Clean the area of the oil pan drainage hole.



16 Screw in the new drainage plug and tighten it. Use a drive socket #19. Use a torque wrench. Tighten it to 30 nm torque.



17 Clean the area of the oil pan drainage hole. Use all-purpose cleaning spray.



18 Lower the car.




19 Remove the oil filler cap.



20 Insert the funnel.



21 Pour oil into the engine through the filler. Required amount of oil: 3.5 l.



Replacement: engine oil and filter – Audi A4 B5 saloon. AUTODOC recommends:

- Use the oil recommended by the manufacturer.

22 Check the oil level using the dipstick. Top up oil if necessary.



Please note!

- The oil level should be between the Min and Max marks.

23 Install the oil filler cap.




24 Tighten the oil filler cap.

25 Run the engine for a few minutes.



26 After the oil pressure warning light goes out, stop the engine.

27 Check the oil level 5 minutes after the stop of the engine operation using a dipstick and add oil if necessary.




Please note!

- The oil level should be between the Min and Max marks.
- Make sure that the oil filler cap is properly tightened.
- Check the threaded plug of the drainage hole and the oil filter seal for tightness. If necessary, carefully tighten them up.

28 Remove the fender protection cover.



29 Close the hood.



Replacement: engine oil and filter – Audi A4 B5 saloon. Tip:


- Note that oil pressure warning light, which indicates insufficient pressure in the lubrication system, may be on for a longer time than usual. After a few seconds, the oil will fill all the channels, and the light will go out.
- To protect the environment from pollution, be sure to dispose of the used filters at special collection points.

WELL DONE!

VIEW MORE TUTORIALS

AUTODOC — TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR AUDI

OIL FILTER: A WIDE SELECTION

CHOOSE CAR PARTS FOR AUDI A4 B5 SALOON

OIL FILTER FOR AUDI: BUY NOW

OIL FILTER FOR AUDI A4 B5 SALOON: THE BEST DEALS & OFFERS

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.